

Performance Criteria

Model :- GSR017

General Overview:

Introducing the **KPT Twin-Lobe Roots Blower** built for **Continuous Duty** operation. Compact and robust, this machine is engineered to deliver performance aligned with **BS: 1571-Part II** and **ISO1217:2009** standards.

-
- | | | | |
|---|---|----|-----------------|
| 1 | Type | :- | Twin Lobe Roots |
| 2 | Discharge Size | :- | 65 NB |
| 3 | Bare Blower Weight | :- | Approx.40 kg. |
| 4 | Design (sea level) ambient conditions are 1013 mbar & 45°C. | | |
-

Performance Specifications (As per design tolerance):

- | | | | |
|---|----------------------------|----|---------------------------|
| 1 | Discharge Capacity (FAD) | :- | 20-320 m ³ /hr |
| 2 | Maximum Discharge Pressure | :- | 703 Mbar |
| 3 | Maximum Operating Speed | :- | 4000 |
| 4 | Drive Type | :- | Belt Driven |
-

Material Specification:

- | | | | |
|---|--------------|----|---|
| 1 | Casing | :- | The Case and Housing are made up of high quality grey cast iron with Xylon coating. |
| 2 | Rotors | :- | The Rotors and Shafts, designed with ample rigidity and strength, are cast as a single unit using high-tensile spheroidal graphite iron with Xylon coating. |
| 3 | Bearings | :- | At drive end, grease lubricated single row roller bearings are used. At gear end, oil lubricated double row angular contact ball bearings are used. |
| 4 | Shaft Sleeve | :- | Shaft sleeve is of EN-8D or Equivalent Material. |
| 5 | Shaft Seal | :- | Viton Oil Seal is used. |
-

Note :- Each blower undergoes individual testing, and test certificates are issued as per request. Technical specifications are subject to customization as per client requirement